Transfer settings

MiniMed™ 770G pump to MiniMed™ 780G pump

Step 1: Copy your current settings onto the Insulin Pump Settings Form. If for any reason you cannot copy the settings, please contact your healthcare professional.

Step 2: Insert a AA battery into your new pump. You can use either a lithium, alkaline, or rechargeable battery.

Step 3: Follow the instructions found in this guide to enter the settings that you have recorded on the Insulin Pump Settings Form into your new pump. For additional information on your pump, please consult the MiniMedTM 770G User Guide.





elivery settings	Delivery settings (cont.)				
olus wizard setup	Bolus increment:				
enu > Options > Delivery Settings > Bolus Estimate Setup	Menu > Options > Delivery Settings > Bolus Increment				
olus Wizard: □ On □ Off	□ 0.025U □ 0.05U □ 0.1U				
arb Ratio:	Max basal/bolus:				
:00A g/U	Menu > Options > Delivery Settings > Max Basal/Bolus				
g/U	Max Basal: U/hr Max Bolus: U				
g/U	Easy bolus:				
sulin Sensitivity Factor:	Menu > Options > Delivery Settings > Easy Bolus				
OOA	□On □Off Step SizeU				
:00A mmol/L per U	Auto suspend:				
mmol/L per U	Menu > Options > Delivery Settings > Auto Suspend				
mmol/L per U	□ On hr □ Off				
Target:	Bolus speed:				
:00A mmol/L	Menu > Options > Delivery Settings > Bolus Speed				
mmol/L	☐ Standard ☐ Quick				
mmol/L					
tive Insulin Time: hr	Utilities				
isal pattern setup					
enu > Basal > Delivery Settings > Basal Pattern Setup	Turn sensor on:				
sal 1: Basal Pattern Name:	Menu > Options > Utilities > Sensor Settings Sensor: □ On □ Off				
:00A U/hr					
	Display options:				
	Menu > Options > Utilities				
eset temp setup	Brightness:				
enu > Options > Delivery Settings > Preset Temp Setup	Auto mode:				
eset Temp Name:	Menu > Options > SmartGuard Auto Mode: □ On □ Off				
pe Percent% Duration hr	Auto Mode: □ On □ Off Auto Mode BG alert: □ On □ Off				
ual/square wave:	Auto Mode by alert: Li On Li Oli				
enu > Options > Delivery Settings > Dual/Square Wave					
ual: □On □Off Square: □On □Off					
eset bolus setup					
enu > Options > Delivery Settings > Preset Bolus Setup					
eset Bolus Name:					
olus: U Type:					
NowSquare Durationhr					

High Limit	Alert before high	Time before high	Alert on high	Rise Alert	Rise Limit*			
12:00A mmol/L	□On	min	□On	□ On	Custommmol/L/min or 1 11 111			
mmol/L	□On	min	□On	□ On	Custommmol/L/min or 1 11 111			
mmol/L	□On	min	□On	☐ On	Custommmol/L/min or 1 11 111			
Snooze Menu > Options > SmartGuard > Snooze > High Snooze: minutes								

Sensor settings: Low settings Menu > Options > SmartGuard > Low Setup

Low Limit	Alert before low	Alert on low	Suspend before low	Suspend on low	Resume basal alert**			
12:00A mmol/L	□On	□On	□On	□On	☐ On			
mmol/L	□On	□On	□On	□On	□ On			
mmol/L	□On	□On	□On	□On	□ On			
Snooze Menu > Options > SmartGuard > Snooze > Low Snooze: minutes								

^{*}Option only available when Rise Alert is on
**Option only available when Suspend on low or Suspend before low is on

Startup wizard

Once you've inserted the battery, the pump powers up and the **Startup Wizard** begins, it will guide you through setting language, time format, and current time and date.

- 1. Select English.
- When the Select Time Format screen appears, select a 12 Hour or a 24 Hour time format.
- 3. When **Enter Time** screen appears, the hour will be flashing. Press ∧ or ∨ to the correct hour and press ○.
- The minutes will be flashing.
 Press ∧ or ∨ to the correct minutes and press ○.
- The AM / PM will be flashing. Press ∧ or ∨ if needed and press ○.
 Select Next.
- 6. When the **Enter Date** screen appears, select **Year**. Press ∧ or ∨ to the correct year and press O. Repeat this step to set up **Month** and **Day**. Select **Next**.
- 7. The rewinding screen will briefly appear, followed by a confirmation message. Select Ok.



Setting max basal

Menu > > Delivery Settings

- 1. Select Max Basal/Bolus and press O.
- 2. Select **Max Basal** to enter the **U/hr** amount. Use ∧ or ∨ to set the **Max Basal** amount. Press **O**.
- 3. Select Save.





Setting max bolus

Menu > > Delivery Settings

- 1. Select Max Basal/Bolus and press O.
- 2. Select Max Basal to enter the U/hr amount. Use ∧ or ∨ to set the Max Basal amount. Press O.
- 3. Select Save.






Setting basal pattern

- 1. Select Basal 1.
- 2. Select Options, then select Edit.
- 3. Press O to enter **End** time. Press O to leave the **End** time at **12:00A.** If you are setting multiple rates use ∧ or ∨ to change the **End** time and press O.
- 4. Press ∧ to enter **U/hr** and press **O**.
- 5. Continue adding **End** times and basal rates as needed, otherwise select **Done.**
- 6. Review the basal rates. If you need to correct, press to go back to edit mode. If Basal rates are correct select **Save.**





Turn bolus wizard on and setup

Menu > > Delivery Settings > Bolus Wizard Setup

- 1. Select Bolus Wizard to turn On.
- 2. Press ∨ to see the rest of the message then select **Next.**



- 3. Review the description of **Carb Ratio** and select **Next**.
- 4. Press O to enter End time. Press O again to leave the End time at 12:00A. If you are setting multiple Carb Ratios use ∧ or ∨ to change the End time, then press O.
- Press ∧ or ∨ to enter g/U then press O.
 Continue adding End times and Carb Ratios as needed.
- 6. Select **Next** when done.
- 7. Review the description of **Sensitivity Factor** and select **Next.**
- 8. Press O to enter **End** time. Press O again to leave the **End** time at **12:00A**. If you are setting multiple Sensitivity Factors, use ∧ or ∨ to change the **End** time, then press O.
- Press ∧ or ∨ to enter mmol/L per U , then press O.
 Continue adding End times and Sensitivity Factors as needed.
- 10. Select **Next** when done.
- 11. Review the description of **BG Target** and select **Next**.
- 12. Press to enter **End** time. Press again to leave the **End** time at **12:00A.** If you are setting multiple **BG Targets**, use ∧ or ∨ to change the **End** time, then press ○.
- 13. Press \wedge or \vee to enter **Lo** and then press \bigcirc .
- 14. Press \wedge or \vee to enter **Hi** and then press \bigcirc .
- 15. Select **Next** when done.
- 16. Review the description of Active Insulin Time and select Next.
- 17. Press O to enter **Duration** time.
- 18. Press \wedge or \vee to enter **hr** then press \bigcirc .
- 19. Select Save.

The Bolus Wizard setup is now complete.












Turn sensor on

Menu > (> Device Settings

 Select Sensor to turn feature On.
 You can now access the High Alert, Low Alert, and Snooze High & Low menus found in the Alert Settings menu.



Pair the transmitter

Menu > > Pair New Device

- 1. Attach your transmitter to the charger and place next to the pump.
- 2. Select **Search** on the pump and immediately remove the transmitter from the charger.
- The Select Device screen appears with a list of available devices.
 Select the CGM device that matches the serial number (SN) on your transmitter.
- 4. Make sure the serial number on the pump screen and transmitter match and select **Confirm.**

Your pump displays a message if the pump and transmitter are paired successfully. If the Sensor feature is turned on, the Connection icon appears on the Home screen.









Programming high settings

- 1. Select High Alert.
- Press O on the time segment. Press O again to leave the End time at 12:00A. If setting multiple time segments, press A to enter End time of first segment, and press O.
- 3. Press ∧ or ∨ to set **High** limit and press . Press to continue.
- 4. Select each feature you wish to turn on. If a feature is on, select it again to turn it back off.
- 5. Once settings are selected, select **Next** and then select **Done.**
- 6. Verify that settings are correct and select Save.
- 7. If snooze time needs to be changed, press to **Snooze High & Low** and press **O**.
 - Select **High Snooze.** Press ∧ or ∨ to enter the correct time and press O. Select **Save**.

Alert Settings
High Alert
Low Alert
Snooze High & Low
Reminders

12:00 A-12:00 A 13.8 mmod/L
Alert before high
Time before high
Alert on high
Rise Alert
Next

High Setup
12:00 A 12:00 A ---12:00 A 12:00 A ---12:00 A 13.9 mmod/L
Alert on high
Start
12:00 A 12:00 A ---12:00 A 12:00 A ---12:00 A 13.9 mmod/L
Alert on high
Setup
12:00 A 13.9 mmod/L
Alert on high


Your High Setup is now complete.

Programming low settings



- 1. Select Low Alert.
- Press O on the time segment. Press O again to leave the End time at 12:00A. If setting multiple time segments, press ∧ to enter End time of first segment, and press O.
- 3. Press ∧ or ∨ to set **Lo** limit and press O. Press O to continue.
- 4. Select each feature you wish to turn on. If a feature is on, select it again to turn it back off.
- 5. Once settings are selected, select **Next** and then select **Done**.
- 6. Verify that settings are correct and select **Save**.
- 7. If snooze time needs to be changed, press ∨ to Select **Snooze High & Low** and press **O**. Select **Low Snooze**. Press ∧ or ∨ to the correct time and press **O**. Select **Save**.

Your Low Setup is now complete.





Turn SmartGuard on

Menu >

- 1. Select **SmartGuard** to turn SmartGuard Feature **On**.
- 2. Review the message on the screen and select **OK**.
- 3. Review the SmartGuard Checklist to complete all tasks and begin use of the SmartGuard Feature. Press v to view the rest of the checklist.



Programming SmartGuard settings



- 1. Review the **Target**.
- 2. Press O to change.
- 3. Press ∧ or ∨ to enter **Target** and then press O.
- 4. Check to make sure that Auto Correction is set to On. Select Save.



Please take some time to review ALL your entries and ensure they are correct.

In need of technical assistance?

24-Hour Technical Support is here to help

Call 1.800.284-4416

For medical advice, contact your healthcare team.

Note: If you turn SmartGuard on before the 48 hour warm up is complete, you may receive an alert at midnight to Enter a BG for SmartGuard. To avoid this, you may want to wait to turn on SmartGuard on day 3 of your pump wear.